

RAMFLEX INTERLOCK THICKNESS: 8MM

Ramflex Interlock is the version with interlocking square tiles of Ramflex that allow easy and fast procedures of application and removal and represent an ideal solution for renovations, high moisture conditions and temporary applications.



CERTIFICATIONS

- Low VOC (Volatile Organic Compounds) emission
- GREENGUARD & GREENGUARD Gold (UL)
- Class A+ (French scope 2011-321)
- REACH Compliant
- UNI EN ISO 9001
- CE marked product (EN 14041 incl DoP)
- Fire EUROCLASS Cfl-S2 (EN13501)

RAMFLEX INTERLOCK THICKNESS: 8MM



986



920



712



710



741



715



790



707

Thickness: 8 mm
Tiles Dimension: 90 cm x 90 cm
Weight: 12 kg/m²

RAMFLEX INTERLOCK THICKNESS: 8MM



University of California-Riverside, USA

Perfect for:

- Holistic Fitness Classes
- Yoga
- Pilates
- Training
- Mobility and Stability work-outs
- Cardio Equipment Areas
- Soft Weights
- Suspension training
- Functional Frames
- Weight Rooms
- Crossfit®

PERFORMANCE & SAFETY

- Optimal combination of resistance and shock absorption thanks to its double-layered construction
- The product withstands wear from weights and light abrasions thanks to its 2 millimeter-thick rubber surface
- Perfect dimensional stability thanks to the combination of the surface layer and shock-absorbing underlayer
- Easy maintenance - non-porous
- Anti-slip: grants the perfect grip for every workout (even barefoot)

WE INNOVATE.YOU WIN

 **MONDO**