


VINYLSPORT M PERFORMANCE 10 MM



PVC sports flooring for indoor use, supplied in rolls with a constant total thickness of 10 mm.

The flooring is consisting of an embossed wear layer with protective treatment provided with solid color or wood effect, a high density fiberglass-reinforced layer and an expanded vinyl foam backing.

The prefabricated Vinylsport M layer is paired on-site with EVERLAY PROTECTION in 4,7 mm. EVERLAY is a dimensional stable and energy absorbing underlayment composed of reinforced fiberglass layer and expanded PVC foam. The two layers are coupled together, using an appropriate adhesive,

to provide a loose laid system with a uniform thickness of 10 mm.

Due to the outstanding performance of the Everlay underlayment, the system has excellent shock absorption for sport use at the highest safety level. The use of the Everlay cushioned underlayment guarantees the athletic performance of the system while providing protection against moisture coming from subfloor. It is a loose laid system, which significantly extends the product life. The underside of the Everlay has a series of stems in expanded resins that improve the overall stability of the flooring system.

This product is ideal for a multisport indoor hall where different indoor sport competitions are held, such of basketball, handball, volleyball, badminton or futsal.

STANDARDS

This product has been certified to be in compliance with European Standards EN14904 (KA≥ 35%) including Declaration Of Performance (DoP, CE marking) and it is rated Euroclass Cfl-S1 in accordance with EN13501.

This product has been certified in compliance with the following schemes and standards for Indoor Air Quality programs (Volatile Organic Compounds emissions):

- French scope (2011-321): Class A+.
- Italian regulation CAM (Minimum Environmental Criteria) following D.M. 11/01/2017.

This article is produced in compliance with the European Regulation REACH (Registration, Evaluation, Authorization and Restriction of Chemicals).

This product has been rated Non Hazardous by external laboratory in accordance with the European Waste Catalogue. This means that it does not present a subrisk to public health or cause adverse effects on the environment.

This product is designed and manufactured according to UNI EN ISO 9001 certification.

CERTIFICATIONS

Available International Sport Federation certificates for this product:

FIBA Certificate of Approval for Synthetic Flooring Category, Level 2 and 3

BWF Synthetic Flooring Certificate

IHF 2019 Certificate of Approval for Synthetic Floorings

24/09/2019

Mondo keeps the right to modify the characteristics of the products in any moment



COLOR RANGE



This color range is to be used as a guideline only.

MAINTENANCE AND INSTALLATION

The product must be stored and installed in appropriate conditions, including suitable protected premises at guaranteed minimum and maximum temperatures and humidity, as fully described in MONDO's *Storage and Installation Instructions*. The product must be used and maintained following the premises described in MONDO's *Use and Maintenance Instructions*.

DIMENSIONS

Thickness	Length	Width	Weight
10 mm	m	cm	5,7 kg/m ²

For additional product information, please refer to the Technical Data Sheet.