

ADVANCE VULCANIZED

TOUGH MEETS COMFORT



ADVANCE VULCANIZED IS A MULTI-LAYERED FLOORING MADE OF VULCANIZED RUBBER. ITS THREE LAYERS HAVE VARYING DEGREES OF HARDNESS, AND THE COMBINATION MAKES IT HANDS DOWN THE MOST DURABLE MULTIPURPOSE FLOORING AROUND.



CO-VULCANIZED MULTI-LAYER DUAL DUROMETER

Two different layers of solid rubber with their own formulations, vulcanized together to form a continuous, seamless piece of material.



AIR-CELL TECHNOLOGY

Air-filled chambers on the bottom layer compress, then expand, acting like bowstrings and projecting athletes up and forward.



SMOOTH SOLID RUBBER TOP LAYER

Vulcanized rubber surfaces with a smooth finish, for indoor installation. Thanks to its properties, under dry conditions, the rubber naturally ensures a superficial grip, without any need for additional embossing.



ADVANCE VULCANIZED

In basketball, support starts under the feet: the right energy return, stability and grip provide the perfect base for top athletic performance. Advance Vulcanized combines three layers to meet all play needs, from practices to championship finals.

Speed, agility and explosive leaping. Volleyball requires a high-end surface capable of supporting high-performance play. That's Advance Vulcanized.

BETTER GRIP MEANS BETTER PERFORMANCE

The performance layer is made of solid rubber that requires no finishes or surface coatings. It is designed to exceed the toughest friction coefficient standards for high-level play and superior biomechanical performance.

LESS IMPACT, MORE COMFORT

The underlayer's deformable geometric structure increases the flooring elasticity. This results in optimized foot support, exceptional shock absorption and maximized energy return for superior comfort while playing.

MAXIMUM SUPPORT FOR HEAVY LOADS

The load disbursement layer enables Advance Vulcanized to withstand heavy loads, such as sports equipment, bleachers, benches and tables.

DIMENSIONS


THICKNESS

ROLL LENGTH


ROLL WIDTH

8 mm	42'7" (13 m (Min. 6m, Max. 15 m))	6'1" (1.86)
10 mm	42'7" (13 m (Min. 6m, Max. 15 m))	6'1" (1.86)


COLOR RANGE




L35




L14



L25



L41



L40



L54



L70



L73



L86



L08



L06



L62



L92